



NTE3183 & NTE3184 Discrete Blue LED Indicators

Description:

The NTE3183 and NTE3184 are blue source color light emitting diodes made with GaN on SiC. It is recommended that a wrist strap or anti-electrostatic glove be used when handling these devices as static electricity and surge will damage these devices. All devices, equipment, and machinery must be electrically grounded.

Features:

- Low Power Consumption
- Solid State Blue Light Source
 - NTE3183 (Blue Diffused)
 - NTE3184 (Clear Blue)
- Suitable for use in Full Color LED Displays and Indicators in Diagnostic/Analytical Equipment

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Reverse Voltage, V_R	5V
DC Forward Current, I_F	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width), I_F	200mA
Power Dissipation, P_D	105mW
Operating Temperature Range, T_{opr}	-40° to +85°C
Storage Temperature Range, T_{stg}	-40° to +85°C
Lead Temperature (During Soldering, .157 (4mm) below package base, 5sec max), T_L	+260°C

Electro-Optical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Voltage	V_F	$I_F = 20\text{mA}$	—	4.5	5.5	V
Reverse Current	I_R	$V_R = 5\text{V}$	—	10	—	μA
Luminous Intensity NTE3183	I_V	$I_F = 20\text{mA}$	12.5	—	40	mcd
NTE3184			20	—	90	mcd
Viewing Angle NTE3183	$2\theta_{1/2}^1$	Note 1	—	60	—	deg.
NTE3184			—	20	—	deg.

Note 1. Viewing Angle is the off-axis angle at which the luminous intensity is half the axial luminous intensity.

Electro-Optical Characteristics (Cont'd): ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Peak Emission Wave Length	λ_{PEAK}	$I_F = 20\text{mA}$	—	430	—	nm
Spectral Line Half Width	$\Delta\lambda$	$I_F = 20\text{mA}$	—	65	—	nm
Capacitance	C	$V_F = 0, f = 1\text{MHz}$	—	100	—	pF

