



44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089

NTE593 Silicon Diode, High Speed Switch

Description:

The NTE593 is a silicon epitaxial high-speed diode in an SOT-23 type surface mount package. This device is intended for high-speed switching in hybrid thick-film circuits.

Absolute Maximum Ratings:

Continuous Reverse Voltage, V_R	75V
Repetitive Peak Reverse Voltage, V_{RRM}	85V
Non-Repetitive Peak Forward Current ($t = 1s$), I_{FSM}	500mA
Average Rectified Forward Current (Average over any 20ms period, Note 1), $I_{F(Av)}$	250mA
DC Forward Current ($T_A \leq +25^\circ\text{C}$, Note 2), I_F	250mA
Repetitive Peak Forward Current, I_{FRM}	250mA
Total Power Dissipation ($T_A \leq +25^\circ\text{C}$), P_{tot}	200mW
Operating Junction Temperature, T_J	+150°C
Storage Temperature Range, T_{stg}	-65° to +150°C
Thermal Resistance, Junction-to-Ambient (Note 2), R_{thJA}	430K/W

Note 1. Measured under pulse conditions: $t_p \leq 0.5\text{ms}$, $I_{F(AV)} = 150\text{mA}$, $t_{(av)} \leq 1\text{ms}$, for sinusoidal operation.

Note 2. Mounted on a ceramic substrate of .314 (8mm) x .393 (10mm) x .027 (0.7mm).

Electrical Characteristics: ($T_J = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Voltage	V_F	$I_F = 1\text{mA}$	—	—	715	mV
		$I_F = 10\text{mA}$	—	—	855	mV
		$I_F = 50\text{mA}$	—	—	1000	mV
		$I_F = 150\text{mA}$	—	—	1250	mV
Reverse Current	I_R	$V_R = 75\text{V}$	—	—	1	μA
		$V_R = 75\text{V}$, $T_J = +150^\circ\text{C}$	—	—	50	μA
Diode Capacitance	C_d	$V_R = 0$, $f = 1\text{MHz}$	—	—	2	pF
Reverse Recovery Time (When switched from $I_F = 30\text{mA}$ to $I_R = 30\text{mA}$)	t_{rr}	measured at $I_R = 1\text{mA}$, $R_L = 100\Omega$	—	—	6	ns
Recovery Charge (When switched from $I_F = 10\text{mA}$ to $V_R = 5\text{V}$)	Q_s	$R_L = 100\Omega$	—	—	45	pC

