XUY388AA6N2S59

roller-electric sensor XUY - for conveyor - 388 mm - PNP

Main

Range of Product	Telemecanique Photoelectric sensors XU
Series name	Application
Electronic sensor type	Photo-electric sensor
Sensor name	XUY
Sensor design	Roller sensor
Detection system	Diffuse
Type of output signal	Discrete
Discrete output type	PNP
Product Specific Application	Conveyor system



Maximum voltage drop	<2 V 100 mA closed state)
Length	15.28 in (388 mm)

Environment

Product Certifications	CE cULus
Ambient Air Temperature for Operation	32122 °F (050 °C)
Ambient Air Temperature for Storage	-4176 °F (-2080 °C)

Ordering and shipping details

Category	22482-ROLLER CONVEYOR SENSORS
Discount Schedule	DS2
GTIN	3389119628877
Nbr. of units in pkg.	10
Package weight(Lbs)	0.24 lb(US) (0.11 kg)
Returnability	Yes
Country of origin	FR

Packing Units

Package 1 Height	0.040 dm	
Package 1 width	0.040 dm	
Package 1 Length	0.400 dm	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration