

4-Port UK-Style Gang Frame for 6C-Type Insert Module, White

MODEL NUMBER: N042U-WF2-6C





Highlights

- Ideal for completing a data (Ethernet) in-wall wiring installation
- Helps prevent accidental cable damage and hides unattractive wiring
- High-impact plastic construction designed to blend in with your home/office décor

Package Includes

N042U-WF2-6C 4-Port UK-Style Gang Frame, White

British-style gang frame accepts up to 4 compatible 6C-type modules for terminating premise data (Ethernet) applications.

Features

U.K. Gang Frame Connects Your In-Wall Data Cable Line

This gang frame for 6C-type insert modules is ideal for terminating your data communications wiring application, including Gigabit Ethernet. The UK-style N042U-WF2-6C also protects electrical and network cables to help prevent accidental damage to your application.

High-Impact Construction Designed to Blend In Seamlessly with Your Room

This white gang frame measures 86 x 146 millimeters (outer frame) and accepts up to four 25 x 38.5 millimeter 6C-type insert modules. It blends elegantly into any home or office décor for a sleek, professional installation. The ABS plastic construction meets UL 94V-0 flame-retardant standards for protection against fire and high heat.

Specifications

| OVERVIEW | | |
|--------------------------|----------------------|--|
| UPC Code | 037332269553 | |
| Accessory Type | Wall Plate | |
| Technology | Cat5/5e; Cat6; Cat6a | |
| Country/Region | UK | |
| | | |
| PHYSICAL | | |
| Color | White | |
| Material of Construction | ABS | |
| Total Number of Ports | 4 | |



| Unit Dimensions (hwd / in.) | 5.750 x 3.390 x 0.590 | |
|-------------------------------------|---------------------------------|--|
| | | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | 14° to 140°F (-10° to 60°C) | |
| Storage Temperature Range | -40° to 154°F (-40° to 68°C) | |
| Operating Humidity Range | 10% to 90% RH, (Non-Condensing) | |
| Storage Humidity Range | 10% to 90% RH, (Non-Condensing) | |
| | | |
| CONNECTIONS | | |
| Number of Ports | 4 | |
| Side A - Connector 1 | (4) KEYSTONE JACK CUTOUT | |
| | | |
| FEATURES & SPECIFICATIONS | | |
| Antibacterial | No | |
| | | |
| STANDARDS & COMPLIANCE | | |
| Product Certifications | UL 94; UL Listed; cUL Listed | |
| Product Compliance | REACH; RoHS | |
| | | |
| WARRANTY & SUPPORT | | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty | |



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.