



ELECTRONICS, INC.  
44 FARRAND STREET  
BLOOMFIELD, NJ 07003  
(973) 748-5089

## NTE965 Linear Integrated Circuit Voltage Regulator, Negative, -8V, 1A

### Description:

The NTE965 voltage regulator employs current limiting, thermal shutdown, and safe-area compensation which makes it remarkably rugged under most operating conditions. With adequate heat-sinking they can deliver output currents in excess of 1.0 amperes.

### Features:

- No External Components Required
- Internal Thermal Overload Protection
- Internal Short-Circuit Current Limiting
- Output Transistor Safe-Area Compensation

### Absolute Maximum Ratings: ( $T_A = +25^\circ\text{C}$ unless otherwise specified)

Input Voltage, $V_{IN}$ .....	-35V
Internal Power Dissipation, $P_D$ .....	Internally Limited
Derate Above $+25^\circ\text{C}$ .....	$15.4\text{mW}/^\circ\text{C}$
Internal Power Dissipation ( $T_C = +25^\circ\text{C}$ ), $P_D$ .....	Internally Limited
Derate Above $+75^\circ\text{C}$ .....	$200\text{mW}/^\circ\text{C}$
Maximum Junction Temperature Range, $T_J$ .....	$-55^\circ$ to $+150^\circ\text{C}$
Storage Temperature Range, $T_{stg}$ .....	$-65^\circ$ to $+150^\circ\text{C}$
Thermal Resistance, Junction-to-Ambient, $R_{thJA}$ .....	$65^\circ\text{C}/\text{W}$
Thermal Resistance, Junction-to-Case, $R_{thJC}$ .....	$5^\circ\text{C}/\text{W}$

### Electrical Characteristics: ( $V_{IN} = -14\text{V}$ , $I_O = 500\text{mA}$ , $T_J = 0^\circ$ to $+125^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Output Voltage	$V_O$	$T_J = +25^\circ\text{C}$		-7.7	-8.0	-8.3	V
		$5\text{mA} \leq I_O \leq 1\text{A}$ , $P_O \leq 15\text{W}$ , $-23\text{V} \leq V_{IN} \leq -10.5\text{V}$		-7.6	-8.0	-8.4	V
Line Regulation	$\text{Reg}_{\text{Line}}$	$T_J = +25^\circ\text{C}$ , Note 1	$-25\text{V} \leq V_{IN} \leq -10.5\text{V}$	-	12	160	mV
			$-17\text{V} \leq V_{IN} \leq -11\text{V}$	-	5	80	
Load Regulation	$\text{Reg}_{\text{Load}}$	$T_J = +25^\circ\text{C}$ , Note 1	$5\text{mA} \leq I_O \leq 1.5\text{A}$	-	45	160	mV
			$250\text{mA} \leq I_O \leq 750\text{mA}$	-	16	80	

**Electrical Characteristics:** ( $V_{IN} = -14V$ ,  $I_O = 500mA$ ,  $T_J = 0^\circ$  to  $+125^\circ C$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Quiescent Current	$I_B$	$T_J = +25^\circ C$	—	4.3	8.0	mA
Quiescent Current Change	$\Delta I_B$	$-25V \leq V_{IN} \leq -10.5V$	—	—	1.0	mA
		$5mA \leq I_O \leq 1A$	—	—	0.5	
Ripple Rejection	RR	$21.5V \leq V_{IN} \leq 11.5V$ , $f = 120Hz$	—	62	—	dB
Dropout Voltage	$V_{IN} - V_O$	$T_J = +25^\circ C$ , $I_O = 1A$	—	2.0	—	V
Output Noise Voltage	$V_n$	$T_A = +25^\circ C$ , $10Hz \leq f \leq 100kHz$	—	10	—	$\mu V/V_O$
Output Resistance	$r_O$	$f = 1kHz$	—	18	—	$m\Omega$
Short-Circuit Current Limit	$I_{sc}$	$T_A = +25^\circ C$ , $V_{IN} = 35V$	—	0.2	—	A
Peak Output Current	$I_{max}$	$T_J = +25^\circ C$	—	2.2	—	A
Average Temperature Coefficient of Output Voltage	$TCV_O$		—	-0.6	—	$mV/^\circ C$

Note 1. Load and line regulation are specified at constant junction temperature. Changes in  $V_O$  due to heating effects must be taken into account separately. Pulse testing with low duty cycle is used.

