



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE2699
Silicon NPN Transistor
Driver for DC-DC Converter
(Compl to NTE2701)
TO-220 Full Pack Type Package

Features:

- Collector-Emitter Sustaining Voltage: $V_{CE(sus)} = 60V$ Min
- High DC Current Gain: $h_{FE} \geq 150$ (Min) @ $V_{CE} = 2V$, $I_C = 3A$
- Low saturation Voltage: $V_{CE(sat)} = 300mV$ (Max) @ $I_C = 8A$, $I_B = 400mA$

Applications:

- Driver for DC/DC Converter
- Actuator Driver

Absolute Maximum Ratings: ($T_A = +25^\circ C$ unless otherwise specified)

Collector-Base Voltage, V_{CBO}	100V
Collector-Emitter Voltage, V_{CEO}	60V
Emitter-Base Voltage, V_{EBO}	7V
Collector Current, I_C		
Continuous	15A
Pulse	30A
Continuous Base Current, I_B	7.5A
Total Power Dissipation, P_T		
$T_C = +25^\circ C$	30W
$T_A = +25^\circ C$	2.0W
Operating Junction Temperature, T_J	+150°C
Storage Temperature Range, T_{stg}	-55° to +150°C

Electrical Characteristics: ($T_C = +25^\circ C$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector-Emitter Sustaining Voltage	$V_{CEO(sus)}$	$I_C = 50mA$, $I_B = 0$	60	—	—	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 8A$, $I_B = 400mA$	—	—	0.3	V
		$I_C = 12A$, $I_B = 600mA$	—	—	0.5	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = 8A$, $I_B = 400mA$	—	—	1.2	V
		$I_C = 12A$, $I_B = 600mA$	—	—	1.5	V
Collector Cut-Off Current	I_{CBO}	$V_{CB} = 60V$, $I_E = 0$	—	—	10	μA
	I_{CEO}	$V_{CE} = 60V$, $I_B = 0$	—	—	1.0	mA
Emitter Cut-Off Current	I_{EBO}	$V_{EB} = 5V$, $I_C = 0$	—	—	10	μA
DC Current Gain	h_{FE}	$I_C = 3A$, $V_{CE} = 2V$	150	—	300	



