


Part Number: PTS25D/30
Proximity Switch - Hall Effect
Threaded - Suggested Magnet: PTSM

PICTURE



✓RoHS Compliant

OPERATIONAL DIAGRAM




FEATURES

- Resistant to Severe Environmental Conditions
- Case Material: Brass/Nickel Plated
- Wire: 3 x Round 7/0.2 PVC Insulated
(White: +12 VDC, Green: 0V, Brown: 0/P)
- Short Circuit and Reverse Polarity Protected
- LED Indication

DIMENSIONS

Drawings not to scale.
 All dimensions in inches (mm) nominal.



SPECIFICATION

Supply Voltage	VDC	10 Min. / 15 Max.
Quiescent Current	Max. mA	25
Sensing Distance	Typ. mm	8
Output Type	5V	Logic gate (Pull Down)
Output Loading		4K7
Continuous Temperature Range	Deg °C	-20° +85°
Intermittent Temperature Range	Deg °C	-20° +105°
Storage Temperature Range	Deg °C	-25° +90°

Note 1: Output is current limited to 800mA and junction temperature limited if current in excess of 800mA is attempted.

As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.

Phone: (1) 973 777 6900 www.comus-intl.com Fax: (1) 973 777 8405

Belgium: + 32 (0)12 390400 - Comus Europe Ltd (Assemtech) UK: +44 (0) 1255 862236 - Germany: +49 (0)911 923 15 943 - Netherlands: +31(0)45 54 39 345 - India: +(91) (44) 43219090
 ©2015 Copyright Comus International, 454 Allwood Road, Clifton NJ 07012, USA