XZCB4L0050

PvR cable, 4 x 0.5 mm2, length 50 m



Main

Accessory / Separate Cable
Part Type

Complementary

Complementary		
Accessory / separate part designation	Bare cable	
Accessory / separate part category	Cabling accessories	
Cable length	164.04 ft (50 m)	
Material	PvR (PVC/NBR) sheath	
Color	Matt black	
Cable cross section	0.00 in² (0.5 mm²)	
Total number of wires	4	
Wire insulation material	PVC	
Flame retardance	Class C2 conforming to NF C 32-070	
[Ue] rated operational voltage	300 V	
[Ui] rated insulation voltage	2000 V NF C 32-201-1	
Bending radius	Minimum 3 x external diameter	
Tensile strength	1035 N/mm²	
Hardness	70 shores A +/-5)	
Net Weight	4.89 lb(US) (2.22 kg)	

Environment

Ambient Air Temperature for Operation	-31194 °F (-3590 °C)
Ambient Air Temperature for Storage	-40212 °F (-40100 °C)
Environmental characteristic	Mineral resistant at 90 °C Without unmoulding agent Synthetic oils at 90 °C Soluble resistant at 90 °C

Ordering and shipping details

Category	22499-SENSORS ACCESSORIES	
Discount Schedule	DS2	
GTIN	3389110197235	
Nbr. of units in pkg.	1	
Package weight(Lbs)	4.96 lb(US) (2.25 kg)	
Returnability	No	
Country of origin	FR	

Packing Units

0	
Unit Type of Package 1	PCE
Package 1 Height	2.17 in (5.5 cm)
Package 1 width	9.06 in (23 cm)
Package 1 Length	9.06 in (23 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	4
Package 2 Weight	20.38 lb(US) (9.246 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes

Contractual warranty

Warranty	18 months	