



NTE293 (NPN) & NTE294 (PNP) **Silicon Complementary Transistors** **Audio Amplifier and Driver**

Description:

The NTE293 (NPN) and NTE294 (PNP) are silicon complementary transistors in a Giant TO92 type package designed for use in low-frequency power amplification and drive applications.

Features:

- Low Collector-Emitter Saturation Voltage

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Collector-Base Voltage, V_{CBO}	60V
Collector-Emitter Voltage, V_{CEO}	50V
Emitter-Base Voltage, V_{EBO}	5V
Collector Current, I_C	
Continuous	1A
Peak	1.5A
Collector Power Dissipation, P_C	1W
Operating Junction Temperature, T_J	+150°C
Storage Temperature Range, T_{stg}	-55° to +150°C

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 10\mu\text{A}, I_E = 0$	60	—	—	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 2\text{mA}, I_B = 0$	50	—	—	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 10\mu\text{A}, I_C = 0$	5	—	—	V
Collector Cutoff Current	I_{CBO}	$V_{CB} = 20\text{V}, I_E = 0$	—	—	0.1	μA
DC Current Gain	h_{FE}	$V_{CE} = 10\text{V}, I_C = 500\text{mA}$, Note 2	120	—	240	
		$V_{CE} = 5\text{V}, I_B = 1\text{A}$, Note 2	50	100	—	
Collector-Emitter Saturation Voltage	$V_{CE(\text{sat})}$	$I_C = 500\text{mA}, I_B = 50\text{mA}$, Note 2	—	0.2	0.4	V
Base-Emitter Saturation Voltage	$V_{BE(\text{sat})}$	$I_C = 500\text{mA}, I_B = 50\text{mA}$, Note 2	—	0.85	1.2	V
Current-Gain Bandwidth Product	f_T	$V_{CB} = 10\text{V}, I_E = 50\text{mA}, f = 200\text{MHz}$	—	200	—	MHz
Collector Output Capacitance	C_{ob}	$V_{CB} = 10\text{V}, I_e = 0, f = 1\text{MHz}$	—	11	20	pF

Note 1. NTE293MP is a matched pair of NTE293 with their DC Current Gain (h_{FE}) matched to within 10% of each other.

Note 2. Pulse measurement.

