NSYDCE2410

Cable entry matrix 24/10. Systems for introduction of premanufactured cables.





Main

Range	Spacial
Product or Component Type	Cable entry plate for connector
Accessory / separate part category	Cable management accessory
Device Application	Multi-purpose
Range compatibility	Spacial S3D compact enclosure Spacial CRN compact enclosure Spacial SF suitable enclosure Spacial S3CM control enclosure Spacial SBM industrial box Thalassa PLA suitable enclosure Thalassa PHD suitable enclosure Thalassa PLM compact enclosure Thalassa PLM insulating modular box
Device composition	1 fixing elements 1 plate
Quantity per Set	Set of 1

Complementary

Accessory / separate part destination	Connector	
Mounting Support	Body of enclosure	
	Cable gland plate	
Material	polyamide	
Fixing mode	By fixing element	
Total cable entry number	10	
Cable entry number	10	
Height	Real 0.55 in (14 mm)	
Width	Real 5.75 in (146 mm)	
	Cut-out 4.41 in (112 mm)	
	Fixing center 5.12 in (130 mm)	
Depth	Real 2.28 in (58 mm)	
	Cut-out 1.42 in (36 mm)	
	Fixing centre 1.26 in (32 mm)	
Net Weight	0.30 lb(US) (0.136 kg)	

Environment

IP degree of protection	IP54	

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480168628
Nbr. of units in pkg.	1
Package weight(Lbs)	4.80 oz (136.0 g)
Returnability	No
Country of origin	ES
<u>-</u>	

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.69 in (17 cm)
Package 1 width	3.15 in (8 cm)
Package 1 Length	1.57 in (4 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	1
Package 2 Weight	4.80 oz (136.0 g)
Package 2 Height	0.79 in (2 cm)
Package 2 width	2.36 in (6 cm)
Package 2 Length	5.91 in (15 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

on a dotal and a d		
Warranty	18 months	